

Chapter 7': SQL – Data Retrieval

Content:

- More features for data retrieval in SQL: Aggregation, more joins and case.

Next:

- Physical data organization: data manipulation

Skeleton SQL Query

select	<Attribute_list>	5
from	<Relation_list>	1
[where	<Predicate_list>	2
group by	<Attribute_list>	3
having	<Predicate_list>	4
order by	<Attribute_list>]	6

Aggregates and Grouping

```
select avg(semester)
from students;
```

Students			
StudNr	Name	Semester	birthdate
24002	Xenokrates	12	1989-03-14
25403	Jonas	12	1994-01-14
26120	Fichte	10	1984-05-12
26830	Aristoxenos	3	1993-06-25
27550	Schopenhauer	3	1995-11-03
28106	Carnap	3	1990-08-30
29120	Theophrastos	2	1994-01-14
29555	Feuerbach	2	1993-07-01

Result
1
7.625

Aggregates and Grouping

```
select semester, min(birthdate)
from students
group by semester
```

Students			
StudNr	Name	Semester	birthdate
24002	Xenokrates	12	1989-03-14
25403	Jonas	12	1994-01-14
26120	Fichte	10	1984-05-12
26830	Aristoxenos	3	1993-06-25
27550	Schopenhauer	3	1995-11-03
28106	Carnap	3	1990-08-30
29120	Theophrastos	2	1994-01-14
29555	Feuerbach	2	1993-07-01

Result	
Semester	Semester
12	1989-03-14
10	1984-05-12
3	1990-08-30
2	1993-07-01

Characteristics of Aggregates

- SQL creates one result tuple per group
- All attributes of the **select**-clause—except the aggregated—have to be listed in the **group by**-clause
- NULL value is an own group
- Aggregats **avg, max, min, count, sum**

Aggregates and Grouping

Find C4 professors that work for at most 8 hours a week on teaching.

Professors			
PersNr	Name	Level	Room
2125	Sokrates	C4	226
2126	Russel	C4	232
2127	Kopernikus	C3	310
2133	Popper	C3	52
2134	Augustinus	C3	309
2136	Curie	C4	36
2137	Kant	C4	7

Students		
StudNr	Name	Semester
24002	Xenokrates	18
25403	Jonas	12
26120	Fichte	10
26830	Aristoxenos	8
27550	Schopenhauer	6
28106	Carnap	3
29120	Theophrastos	2
29555	Feuerbach	2

Lectures			
Lecture Nr	Title	Weekly Hours	Given_by
5001	Grundzüge	4	2137
5041	Ethik	4	2125
5043	Erkenntnistheorie	3	2126
5049	Mäeutik	2	2125
4052	Logik	4	2125
5052	Wissenschaftstheorie	3	2126
5216	Bioethik	2	2126
5259	Der Wiener Kreis	2	2133
5022	Glaube und Wissen	2	2134
4630	Die 3 Kritiken	4	2137

attend	
StudNr	LectureNr
26120	5001
27550	5001
27550	4052
28106	5041
28106	5052
28106	5216
28106	5259
29120	5001
29120	5041
29120	5049
25403	5022
29555	5022
29555	5001

require	
Predecessor	Successor
5001	5041
5001	5043
5001	5049
5041	5216
5043	5052
5041	5052
5052	5259

test			
StudNr	LectureNr	PersNr	Grade
28106	5001	2126	1
25403	5041	2125	2
27550	4630	2137	2

Assistants			
PersNr	Name	Area	Boss
3002	Platon	Ideenlehre	2125
3003	Aristoteles	Syllogistik	2125
3004	Wittgenstein	Sprachtheorie	2126
3005	Rhetikus	Planetenbewegung	2127
3006	Newton	Keplersche Gesetze	2127
3007	Spinoza	Gott und Natur	2126

Aggregates and Grouping

Find C4 professors that work for at most 8 hours a week on teaching.

```
select persNr, name, sum (weeklyHours)
from Lectures, Professors
where givenby = persNr and level = 'C4'
group by persNr, name
having sum (weeklyHours) <= 8;
```


Example Execution

In the following slides we step through the (logical) execution of the following query:

```
select persNr, name, sum (weeklyHours)
from Lectures, Professors
where givenby = persNr and level = 'C4'
group by persNr, name
having sum (weeklyHours) <= 8;
```

1. Cross Product

from Lectures, Professors							
Lecture Nr	Title	Weekly Hours	Given_by	PersNr	Name	Level	Room
5001	Grundzüge	4	2137	2125	Sokrates	C4	226
5041	Ethik	4	2125	2133	Popper	C3	52
...
4630	Die 3 Kritiken	4	2137	2137	Kant	C4	7

↓ Next: **where**-clause

2. Where Filtering

where level = 'C4'

Lecture Nr	Title	Weekly Hours	Given_by	PersNr	Name	Level	Room
5001	Grundzüge	4	2137	2125	Sokrates	C4	226
5041	Ethik	4	2125	2125	Sokrates	C4	226
...
4630	Die 3 Kritiken	4	2137	2137	Kant	C4	7

↓ Next: **join** condition

3. Join Condition

where givenby = persNr

Lecture Nr	Title	Weekly Hours	Given_by	PersNr	Name	Level	Room
5001	Grundzüge	4	2137	2137	Kant	C4	7
5041	Ethik	4	2125	2125	Sokrates	C4	226
5043	Erkenntnistheorie	3	2126	2126	Russel	C4	232
5049	Mäeutik	2	2125	2125	Sokrates	C4	226
4052	Logik	4	2125	2125	Sokrates	C4	226
5052	Wissenschaftstheorie	3	2126	2126	Russel	C4	232
5216	Bioethik	2	2126	2126	Russel	C4	232
4630	Die 3 Kritiken	4	2137	2137	Kant	C4	7

↓ Next: group by

4. Grouping

group by persNr, name

Lecture Nr	Title	Weekly Hours	Given_by	PersNr	Name	Level	Room
5041	Ethik	4	2125	2125	Sokrates	C4	226
5049	Mäeutik	2	2125	2125	Sokrates	C4	226
4052	Logik	4	2125	2125	Sokrates	C4	226
5043	Erkenntnistheorie	3	2126	2126	Russel	C4	232
5052	Wissenschaftstheo.	3	2126	2126	Russel	C4	232
5216	Bioethik	2	2126	2126	Russel	C4	232
5001	Grundzüge	4	2137	2137	Kant	C4	7
4630	Die 3 Kritiken	4	2137	2137	Kant	C4	7

↓ Next: **having** filtering

5. Having Filtering

`having sum (weeklyHours) <= 8;`

Lecture Nr	Title	Weekly Hours	Given_by	PersNr	Name	Level	Room
5043	Erkenntnistheorie	3	2126	2126	Russel	C4	232
5052	Wissenschaftstheo.	3	2126	2126	Russel	C4	232
5216	Bioethik	2	2126	2126	Russel	C4	232
5001	Grundzüge	4	2137	2137	Kant	C4	7
4630	Die 3 Kritiken	4	2137	2137	Kant	C4	7



Next: Select aggregation (**sum**) and projektion

Result

```
select persNr, name, sum (weeklyHours)
```

PersNr	Name	sum (WeeklyHours)
2126	Russel	8
2137	Kant	8

Maximum / Minimum

Student with the highest StudNr

```
select StudNr, Name
from Students
where StudNr =
    (select max(StudNr)
     from Student);
```

NOT

```
select Name, max(StudNr)
from Students;
```


Example

Find students who attend more than two lecture.

StudNr	Name	Number_of_Lectures
28106	Carnap	4
29120	Theophrastos	3

Example - Solution

```
select s.StudNr, s.Name, count(*) as Number_of_Lectures
from Students s, attend a
where s.StudNr = a.StudNr
group by s.StudNr, s.Name
having count(*) > 2;
```

StudNr	Name	Number_of_Lectures
28106	Carnap	4
29120	Theophrastos	3

Example - Instead of having, a Sub-Query could be used

```
select tmp.StudNr, tmp.Name, tmp.Number_of_Lectures
from (select s.StudNr, s.Name, count(*) as Number_of_Lectures
from Students s, attend a
where s.StudNr=a.StudNr
group by s.StudNr, s.Name) tmp
where tmp. Number_of_Lectures > 2;
```

StudNr	Name	Number_of_Lectures
28106	Carnap	4
29120	Theophrastos	3

Case Construct

```
select StudNr, ( case when Grade < 1.5 then 'very good'  
                when Grade < 2.5 then 'good'  
                when Grade < 3.5 then 'satisfactory'  
                when Grade < 4.0 then 'sufficient'  
                else 'failed' end)  
  
from test;
```

First qualifying **when**-clause is executed

Joins in SQL-92

- **(cross join)**: full cartesian product (not in all DBS!)
- **(natural join)**: equality test on all attributes with the same names, output of all attributes, those with the same names only once (not in all DBS!)
- **semi-join**: no operator in SQL, expressed with **exists** or **in** or **join + select**, only keeps attributes of either side
- **outer-join**: keeps tuples that do not find a join partner and fills them with null
- **inner-join**: not an outer-join

Joins in SQL-92

- **Inner-joins:**
 - Theta Join (any conditions)
 - Equi-join (only equal condition)

Name	StudNr
Carnap	1
Fichte	2

StudNr	LectureNr
2	Databases
2	Math

(Inner) Join

```
select *  
from  $R_1, R_2$   
where  $R_1.A = R_2.B;$ 
```

or alternatively

```
select *  
from  $R_1$  join  $R_2$  on  $R_1.A = R_2.B;$ 
```

Joins in SQL-92

- **left, right or full [outer] join**: keeps tuples with no join partner

Name	StudNr
Carnap	1
Fichte	2

StudNr	LectureNr
2	Databases
2	Math

Outer Joins (left)

```
select p.PersNr, p.Name, t.PersNr, t.Grade,  
        t.StudNr, s.StudNr, s.Name  
from (Professors p  
        left outer join test t  
            on p.PersNr = t.PersNr)  
        left outer join Students s  
            on t.StudNr = s.StudNr;
```

Result

p.PersNr	p.Name	t.PersNr	t.Grade	t.StudNr	s.StudNr	s.Name
2126	Russel	2126	1	28106	28106	Carnap
2125	Sokrates	2125	2	25403	25403	Jonas
2137	Kant	2137	2	27550	27550	Schopenhauer
2136	Curie	null	null	null	null	null
⋮	⋮	⋮	⋮	⋮	⋮	⋮

Outer Joins (right)

```
select p.PersNr, p.Name, t.PersNr, t.Grade,  
        t.StudNr, s.StudNr, s.Name  
from (Professors p  
        right outer join test t  
            on p.PersNr = t.PersNr)  
        right outer join Students s  
            on t.StudNr = s.StudNr;
```

Result

p.PersNr	p.Name	t.PersNr	t.Grade	t.StudNr	s.StudNr	s.Name
2126	Russel	2126	1	28106	28106	Carnap
2125	Sokrates	2125	2	25403	25403	Jonas
2137	Kant	2137	2	27550	27550	Schopenhauer
null	null	null	null	null	26120	Fichte
⋮	⋮	⋮	⋮	⋮	⋮	⋮

Outer Joins (full)

```
select p.PersNr, p.Name, t.PersNr, t.Grade,  
        t.StudNr, s.StudNr, s.Name  
from (Professors p  
        full outer join test t  
            on p.PersNr = t.PersNr)  
        full outer join Students s  
            on t.StudNr = s.StudNr;
```

Result

p.PersNr	p.Name	t.PersNr	t.Grade	t.StudNr	s.StudNr	s.Name
2126	Russel	2126	1	28106	28106	Carnap
2125	Sokrates	2125	2	25403	25403	Jonas
2137	Kant	2137	2	27550	27550	Schopenhauer
2136	Curie	null	null	null	null	null
null	null	null	null	null	26120	Fichte
⋮	⋮	⋮	⋮	⋮	⋮	⋮

Example: Null values

Aggregates on a column containing **some** null values:

```
select sum(semester), --  
       count(semester), --  
       count(*), --  
       avg(semester) --  
from Students
```

Results:

?
?
?
?

Students		
StudNr	Name	Semester
27550	Schopenhauer	4
25403	Jonas	null
26120	Fichte	10

Example: Null values

Aggregates on a column containing **some** null values:

```
select sum(semester),      -- 14
       count(semester),   -- 2
       count(*),          -- 3
       avg(semester)      -- 7
from Students
```

Students		
StudNr	Name	Semester
27550	Schopenhauer	4
25403	Jonas	null
26120	Fichte	10

Example: Null values

Aggregates on a column containing **only** null values:

```
select sum(semester), --  
       count(semester), --  
       count(*), --  
       avg(semester) --  
from Students  
where stdNr = 25403
```

Results:

?
?
?
?

Students		
StudNr	Name	Semester
27550	Schopenhauer	4
25403	Jonas	null
26120	Fichte	10

Example: Null values

Aggregates on a column containing **only** null values:

```
select sum(semester),      -- null
       count(semester),  -- 0
       count(*),          -- 1
       avg(semester)      -- null
from Students
where stdNr = 25403
```

Students		
StudNr	Name	Semester
27550	Schopenhauer	4
25403	Jonas	null
26120	Fichte	10

Example: Null values

Aggregates on a column containing **no** values:

```
select sum(semester), --  
       count(semester), --  
       count(*), --  
       avg(semester) --  
from Students  
where false
```

Results:

?
?
?
?

Students		
StudNr	Name	Semester
27550	Schopenhauer	4
25403	Jonas	null
26120	Fichte	10

Example: Null values

Aggregates on a column containing **no** values:

```
select sum(semester),      -- null
       count(semester),  -- 0
       count(*),         -- 0
       avg(semester)      -- null
from Students
where false
```

Students		
StudNr	Name	Semester
27550	Schopenhauer	4
25403	Jonas	null
26120	Fichte	10

Exercise SQL

Average Grade of the student Schopenhauer.

Number of given lectures for all professors.

Number of students that a professor knows from lectures.

Exercise SQL (cont.)

```
select name, avg(grade), count(*)  
from students s left outer join test t  
           on s.studnr = t.studnr  
where name = 'Schopenhauer'  
group by name;
```

```
select persNr, name, count(lectureNr) as numLectures  
from Professors p left outer join Lectures l  
           on p.persNr = l.given_by  
where level = 'C4'  
group by p.persNr, p.name  
order by numLectures desc
```